

The 130 Vapor Phase Unit from OMI Industries was developed to provide a “dry” dispersion system for the efficient and economical application of Fresh Wave IAQ[®] Air & Surface odor eliminator.



HOW DOES THE 130 WORK WITHOUT MASKING AGENTS?

The 130 Vapor Phase unit disburses sub-micron size Fresh Wave IAQ molecules into the air. These sub-micron molecules enhance the odor elimination characteristics of Fresh Wave in two ways:

1. The smaller the droplet, the greater the degree of penetration
2. The smaller the droplets, the more Fresh Wave surface area there is to make contact with and eliminate the odor

Properly positioned, the 130 creates an “odor barrier” between garbage odors and the nose of the offended customer, patron, resident or employee.

FEATURES/BENEFITS

- **Broad Spectrum Odor Elimination:** Garbage related odors frequent in Dumpster Rooms, Compactor Rooms, Trash Chutes, Loading Docks, Septic Systems & Grease Traps.
- **Odor Barrier:** With the proper placement of the discharge piping, we can create an invisible curtain of sub-micron sized droplets, preventing odors from moving into the protected area.
- **Easy to Use & Operate:** Determine the appropriate dilution rate based on the severity of your odor challenge and fill the 12 gallon tank with 7 gallons of Fresh Wave OEM Concentrate Solution, plug it in, and turn it on.
- **Safe:** The 130 Vapor Phase Unit and Fresh Wave IAQ are safer to use than an Ozone Generator and faster than a Hydroxyl Generator. There is no need to evacuate the area being treated while the Vapor Phase Unit is in use. You and your employees can work alongside of a Vapor Phase Unit.

SPECIFICATIONS

Dimensions: 24" x 16" x 48"
 Weight: 117 lbs
 Liquid Capacity (Max.): 7 Gal.
 Output: 2-8 pts / 24Hr
 Outlet Size: 2"
 Current Draw: 0.6A
 Power Required: 115V/1P/60Hz

*The standard unit includes a 1/2 NPT electrical service elbow ready for connection to electrical conduit. A 12ft power cord is available as an option.