

The M130 Vapor Phase Unit from OMI Industries was developed to provide a “dry” dispersion system for the efficient and economical application of Fresh Wave IAQ® Air & Surface odor eliminator.



SPECIFICATIONS

Dimensions: 18" x 20" x 28"

Weight: 55 lbs

Liquid Capacity (Max.): 2 Gal.

Output: 1-5 pts/24Hr
50-60 CFM Dry Vapor

Outlet Size: 3"

Current Draw: 0.6A

Power Required: 115V/1P/60Hz

*Includes a 12ft power cord with cord wrap.

HOW DOES THE M130 WORK WITHOUT MASKING AGENTS?

The M130 Vapor Phase unit disburses sub-micron size Fresh Wave IAQ molecules into the air. These sub-micron molecules enhance the odor elimination characteristics of Fresh Wave in two ways:

1. The smaller the droplet, the greater the degree of penetration
2. The smaller the droplets, the more Fresh Wave surface area there is to make contact with and eliminate the odor

These minute, dry vapor particles are able to eliminate malodors in the air and on surfaces while also penetrating deep into draperies, upholstery, bedding, wallpaper, carpets and other surfaces.

FEATURES/BENEFITS

- **Broad Spectrum Odor Elimination:** smoke, soot, mildew, trauma scene, skunk, dead rodents, chemical, sewage, fuel oil, food (ex: curry), vomit, feces & urine.
- **Mobile:** easily moves between hotel rooms, rental properties or around a restoration job site. Equipped with swiveling casters as well as side-mounted “lift” handles for moving in and out of transportation vehicles.
- **Easy to Use & Operate:** remove the fill tube cap and fill the tank with a maximum of 2 gallons of Fresh Wave IAQ Air & Surface Liquid (RTU), plug in and turn on.
- **Safe:** the M130 Vapor Phase Unit and Fresh Wave IAQ are safer to use than an Ozone Generator and faster than a Hydroxyl Generator. There is no need to evacuate the area being treated while the Vapor Phase Unit is in use.